

531 - SAFETY GRID™


PRODUCT INFORMATION BROCHURE





For over 70 years, the name Notrax® has meant superior quality, service, and innovative products. Now this brand is a cornerstone of Justrite Safety Group, offering the widest selection of products to a variety of markets and applications including entrance mats, anti-fatigue/safety mats, and products designed specifically for use in professional food service environments. Notrax® offers a complete selection of floor matting options to meet any application requirement, quality expectation, and budget.

- **Track record of manufacturing high quality mats for over seventy years**
- **All products are manufactured in ISO certified facilities**
- **Notrax® offers anti-fatigue matting, entrance matting, safety matting, food service matting and specialty mats designed for a variety of industries**




531- SAFETY GRID™ has a welded duckboard design that creates an elevated platform for safety and keeps traffic away from moisture making it the perfect choice for locker rooms, showers and pool areas. The PVC vinyl compound resists chemicals, while providing an anti-slip surface and basic fatigue relief.

Material: PVC

Features and Benefits:

- Duckboard design constructed of resilient vinyl
- Creates an elevated platform keeping traffic away from moisture
- Top of rails features a saw-tooth design for added traction

⚠ WARNING: This product can expose you to chemicals including di-2-ethylhexyl phthalate and/or diisononyl phthalate which is known to the State of California to cause cancer, birth defects or reproductive harm. For more information, visit www.P65Warnings.ca.gov



MODEL: 531

SPECIFICATIONS

Roll Sizes	2'x40', 3'x40', 4'x40'
Thickness	1/2"
Cut Lengths	2', 3', and 4' widths (up to 40' long)
Colors	<div>  Black  Black/Yellow  Grey  Blue </div>

Performance:

	Good	Better	Best	Superior
Wear Resistance	<div></div>	<div></div>	<div></div>	<div></div>
Anti-fatigue Performance	<div></div>	<div></div>	<div></div>	<div></div>
Slip Resistance	<div></div>	<div></div>	<div></div>	<div></div>

APPLICATIONS

- Elevated Runs
- Locker Rooms
- Shower Areas
- Pool Areas



Oil/Grease Resistant



Cleaning



Floor Protection



Cut Lengths



Anti-Fatigue



Anti-Slip



Drainage

TESTING DATA

Test	Test Description	Results
ASTM C-1028-96	Static Coefficient of Friction	Dry: 0.69 Wet: 0.55
-	Compression Deflection	@ 20 lbs/in2: 0.030 @ 40 lbs/in2: 0.035
ASTM D-1004-94a-03	Tear Strength	45.6 lbs
ASTM D-2240	Durometer (Shore A)	90
ASTM D-3884	Abrasion Resistance	@ 500 cycles: 0.18% @ 1000 cycles: 0.23%
ASTM D-2859/CPSC FF-170	Surface Flammability/Carpets and Rugs	Pass
ASTM D-1894-01	Modified Slip Test: Avg. C.O.F. (Coefficient of Friction)	VCT: 0.38 Painted Concrete: 0.40 Vinyl Flooring: 0.52 Epoxy Painted Concrete: 0.37
ASTM D-412	Breaking Load & Elongation	Breaking Load - 100.25 lbs/in2 Elongation - 184.14%
-	Colorfastness to Light	3 - 4, Noticeable to Slight Change

*Testing performed by an independent test laboratory.

